

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A theft prevention system for protecting a portable electronic device, comprising:

an acceleration sensor, an audio output device, and a controller operatively connected with the acceleration sensor and the audio output device, the acceleration sensor, the audio output, and the controller each being proximate to the portable electronic device, the theft prevention system being configured to:

display a graphical user interface for a user of the portable electronic device to initiate the theft prevention system or to set one or more parameters to be used by the theft prevention system in detecting a theft condition;

sense an acceleration of the portable electronic device by the acceleration sensor, the acceleration sensor producing an acceleration signal;

examine characteristics of the acceleration signal to detect whether a theft condition is present; and

initiate, by the controller, the production of an alarm signal using the audio output device when it is detected that a theft condition is present;

wherein the graphical user interface is configured to:

display a theft detection menu; and

when the theft detection system is not active, receive a user input selection in the theft detection menu for activating the theft detection system;

when the theft detection system is active, receive a user input selection in the theft detection menu for deactivating the theft detection system.

2. (Original) The theft prevention system of claim 1 wherein the controller further comprises a frequency filter electrically connected to the acceleration sensor, the frequency filter being a low-pass filter configured to attenuate frequencies of the acceleration signal characteristic of an impact upon the portable electronic device, so as to detect frequencies of the acceleration signal characteristic of movement of the portable electronic device.
3. (Original) The theft prevention system of claim 2 wherein the controller is further configured to initiate the production of the alarm signal upon detecting the frequencies of the acceleration signal characteristic of movement of the device.
4. (Original) The theft prevention system of claim 1 wherein the portable electronic device further includes a microprocessor operatively connected with the controller and the audio output, the controller configured to transmit to the microprocessor a theft detection signal in response to receiving the acceleration signal, the microprocessor configured to engage the audio output to produce the alarm signal in response to receipt of the theft detection signal.
5. (Original) The theft prevention system of claim 1 wherein the microprocessor is configured to enter a sleep mode so as to conserve electric power, and wherein the theft detection signal directs the microprocessor to awaken from the sleep mode so as to engage the audio output to produce the alarm signal.
6. (Original) The theft prevention system of claim 1 wherein the portable electronic device further comprises a visual output device operatively connected with the controller, the controller further configured to initiate the broadcast of a visual alarm message from the visual output device upon receiving the acceleration signal.

7. (Original) The theft prevention system of claim 6 wherein the controller is further configured to display a visual warning on the visual output device, the visual warning a warning against theft of the portable electronic device.

8. (Canceled)

9. (Currently Amended) A portable electronic device having a system for protecting against theft, comprising:

a housing of the portable electronic device;

an acceleration sensor proximate to the housing and configured to detect an acceleration of the portable electronic device and produce an acceleration signal;

circuitry configured to examine characteristics of the acceleration signal to detect whether a theft condition is present;

an output device; and

a controller configured to display a graphical user interface for a user of the portable electronic device to initiate the theft prevention system or to set one or more parameters to be used by the theft prevention system in detecting a theft condition, and to initiate the output of an alarm using the output device when it is detected that a theft condition is present;

wherein the graphical user interface is configured to:

display a theft detection menu; and

when the theft detection system is not active, receive a user input selection in the theft detection menu for activating the theft detection system;

when the theft detection system is active, receive a user input selection in the theft detection menu for deactivating the theft detection system.

10. (Original) The portable electronic device of claim 9 wherein the controller further comprises a frequency filter electrically connected to the acceleration sensor, the frequency filter a low-pass filter configured to attenuate frequencies of the acceleration characteristic of an impact upon the portable electronic device, and to pass frequencies of the acceleration characteristic of movement of the portable electronic device so as to detect theft of the portable electronic device.

11. (Original) The portable electronic device of claim 10 wherein the controller is further configured to initiate the output of the alarm upon detecting the frequencies of the acceleration characteristic of movement of the device.

12. (Original) The portable electronic device of claim 9 further including a microprocessor electrically connected to the controller and the output device, the controller configured to transmit to the microprocessor a theft detection signal in response to detection of the acceleration by the acceleration sensor, the microprocessor configured to engage the output device to output the alarm in response to receipt of the theft detection signal.

13. (Original) The portable electronic device of claim 9 wherein the microprocessor is configured to enter a sleep mode so as to conserve electric power, and wherein the theft detection signal directs the microprocessor to awaken from the sleep mode so as to engage the output device to output the alarm.

14. (Original) The portable electronic device of claim 9 wherein the output device is an audio output device proximate to the housing and operatively connected with the controller, the

controller further configured to initiate the output of an audible alarm message from the audio output device upon detection of the acceleration by the acceleration sensor.

15. (Original) The portable electronic device of claim 9 wherein the output device is a visual output device proximate to the housing and operatively connected with the controller, the controller further configured to initiate the output of a visual alarm message from the visual output device upon detection of the acceleration by the acceleration sensor.

16. (Original) The portable electronic device of claim 15 wherein the controller is further configured to display a visual warning on the visual output device, the visual warning a warning against theft of the portable electronic device.

17. (Canceled)

18. (Original) The portable electronic device of claim 9 further including a microprocessor operatively connected with the acceleration sensor and the output device, wherein the microprocessor includes the controller.

19. (Currently Amended) A method of protecting a portable electronic device against theft, comprising:

displaying a graphical user interface for a user of the portable electronic device to initiate the theft prevention system or to set one or more parameters to be used by the theft prevention system in detecting a theft condition, wherein the graphical user interface is configured to:

display a theft detection menu; and

when the theft detection system is not active, receive a user input selection in the theft detection menu for activating the theft detection system;

when the theft detection system is active, receive a user input selection in the theft detection menu for deactivating the theft detection system;

monitoring the portable electronic device so as to generate an acceleration signal corresponding to an acceleration of the portable electronic device, the acceleration signal having frequency characteristics of movement of the portable electronic device;

filtering the acceleration signal so as to isolate the frequencies characteristic of movement of the device;

comparing the acceleration signal to an empirically determined frequency profile corresponding to a theft condition so as to determine a metric measuring a correspondence between the frequency profile and the frequency characteristics of movement of the device; and
generating an alarm when the metric indicates that a theft condition is present.

20. (Original) The method of claim 19 wherein the generating further comprises generating an audible alarm.
21. (Original) The method of claim 19 wherein the generating further comprises generating a visual alarm.
22. (Original) The method of claim 19 further comprising displaying a visual warning against theft of the portable electronic device.
23. (Canceled)

24. (Original) The method of claim 19 further comprising updating the frequency profile from time to time.

25-34. (Canceled)

35. (Currently Amended) The theft prevention system of claim 1 34, wherein the user is required to provide a password in the theft detection menu for activating and deactivating the theft detection system.

36. (Previously Presented) The theft prevention system of claim 1 34, wherein the theft detection menu includes user-modifiable settings relating to one or more of: initiation of a theft detection mode, whether an audible alarm and/or a visual alarm is to be utilized when a theft condition is present, a maximum alarm volume, whether a warning message is to be displayed, a sensitivity of the theft detection mode, a ramp-up time to a specified maximum volume, and a password for disabling the theft detection mode.

37. (Canceled)

38. (Currently Amended) The portable electronic device of claim 9 37, wherein the user is required to provide a password in the theft detection menu for activating and deactivating the theft detection system.

39. (Currently Amended) The portable electronic device of claim 9 37, wherein the theft detection menu includes user-modifiable settings relating to one or more of: initiation of a theft detection mode, whether an audible alarm and/or a visual alarm is to be utilized when a theft

condition is present, a maximum alarm volume, whether a warning message is to be displayed, a sensitivity of the theft detection mode, a ramp-up time to a specified maximum volume, and a password for disabling the theft detection mode.

40. (Canceled)

41. (Currently Amended) The method of claim 19 40, wherein receiving a user input selection in the theft detection menu for activating and deactivating the theft detection system includes providing a password.

42. (Currently Amended) The method of claim 19 40, wherein the theft detection menu includes user-modifiable settings relating to one or more of: initiation of a theft detection mode, whether an audible alarm and/or a visual alarm is to be utilized when a theft condition is present, a maximum alarm volume, whether a warning message is to be displayed, a sensitivity of the theft detection mode, a ramp-up time to a specified maximum volume, and a password for disabling the theft detection mode.

43. (Currently Amended) A theft prevention system for protecting a portable electronic device, comprising:

an acceleration sensor, an audio output device, and a controller operatively connected with the acceleration sensor and the audio output device, the acceleration sensor, the audio output, and the controller each being proximate to the portable electronic device, the theft prevention system being configured to:

display a graphical user interface for a user of the portable electronic device to initiate the theft prevention system or to set one or more parameters to be used by the theft prevention system in detecting a theft condition, wherein the graphical user interface is configured to:

display a theft detection menu; and

when the theft detection system is not active, receive a user input selection in the theft detection menu for activating the theft detection system;

when the theft detection system is active, receive a user input selection in the theft detection menu for deactivating the theft detection system;

sense an acceleration of the portable electronic device by the acceleration sensor, the acceleration sensor producing an acceleration signal;

examine characteristics of the acceleration signal to detect whether a theft condition is present; and

initiate, by the controller, the production of an internal theft signal when it is detected that a theft condition is present.

44. (Previously Presented) The theft prevention system of claim 43 wherein the controller further comprises a frequency filter electrically connected to the acceleration sensor, the frequency filter being a low-pass filter configured to attenuate frequencies of the acceleration signal characteristic of an impact upon the portable electronic device, so as to detect frequencies of the acceleration signal characteristic of movement of the portable electronic device.

45. (Previously Presented) The theft prevention system of claim 43 wherein the portable electronic device further comprises a visual output device operatively connected with the controller, the controller further configured to initiate the broadcast of a visual alarm message from the visual output device upon receiving the acceleration signal.

46. (Previously Presented) The theft prevention system of claim 45 wherein the controller is further configured to display a visual warning on the visual output device, the visual warning a warning against theft of the portable electronic device.